

TECHNICAL DATA SHEET

AC80SL

Graffiti Shadow Remover

Code 2540

DESCRIPTION

Graffiti Shadow Remover is a strong alkaline liquid detergent compound. It will remove the residue of most paints left in the pores of substrates as a follow up step to the use of a paint stripper especially when removing graffiti.

FEATURE & BENEFITS

- Safe to use on epoxy coatings and most metals
- Non-toxic and biodegradable
- Contains no phenolics, chlorinated solvents or heavy metal salts

DIRECTIONS FOR USE

Exterior Building Services: Apply by brush or spray use neat or 1:1 water solution of Graffiti Shadow Remover, 3 x 10 minute intervals. After this period hose off with high pressure water. This saturation process helps soften the remaining pigments in the substrate. Best results are achieved with hot water.

PHYSICAL PROPERTIES

Appearance:	Clear, light yellow liquid
Odour:	Nil
Specific Gravity:	1.25
Flash Point:	Nil, Non-flammable
Foaming Properties:	Low to Medium
Rinsability:	Good
pH of 1% Solution:	12.5
Stability:	Good in hot and cold water
Effects on Materials:	Will attack paint & soft metals especially aluminium.

FIRST AID

Graffiti Shadow Remover contains Caustic Soda. Precautions should be taken to protect skin and eyes. Refer to the Material Safety Data for further information.

Ordering Information

Code	Packaging
2540/42	5 Litres
2540/51	20 Litres

All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

Created 6th April 2020 Date Printed 29/04/2021 1:35 PM

